

# BLACK DIAMOND

## Speed Sensors

<p>Magnetic Speed Sensor (A)</p>	<p>High-sensitivity sensor, permits magnetic pickup to be up to ¾" away. Standard sensor provided with all systems. Includes fastening screws and magnet.</p>	
<p>Inductive Proximity Speed Sensor (B)</p>	<p>To detect speed using moving ferrous material, such as bolt heads. Sensor mounts 1-3mm from rotation reference. Specify two-piece assembly or integrated sensor &amp; cable assembly.</p>	<p>Integrated cable/sensor Sensor Only Cable Only</p>
<p>Speed Sensor Collar (C)</p>	<p>Slips over axles and jackshafts, to permit easy installation of speed sensor pickups. Includes one or two magnets per collar.</p>	<p>19, 30, 32, 40, 45, 50mm Diameters</p>

A.



B.



C.



  
**Precision AutoResearch**  
 901 Hillside Drive  
 Bensenville, IL 60106  
 (630) 766-4402  
 PARbrowser@aol.com  
 PrecisionAutoResearch.com



***Speed Sensors***

Belt Speed Sensor (D)	Measure belt slippage separately from clutch movement! Takes clutch tuning to another level beyond mere JS/Engine ratio.	SnoLOG, XG Log, and EVO3 only
GPSpeed (E)	GPS speed sensor. 0-300mph	<a href="#"><u>Click here for full spec sheet.</u></a>

D.



E.



$\phi$   
**Precision *Auto*Research**  
901 Hillside Drive  
Bensenville, IL 60106  
(630) 766-4402  
PARbrowser@aol.com  
PrecisionAutoResearch.com